



## 230v Air/Floor Model PRT-E

### Modern Slimline Appearance

The slimline PRT-E thermostat is flush mounted, resulting in a depth of only 13mm after installation.

### Energy Saving Optimum Start

Most home owners manually allow for a heat up time when programming their heating system. This manual method does not allow for seasonal changes. Optimum start is an energy-saving feature that calculates the amount of heat up time required to ensure your home is warm when you wake and return home from work. The thermostat will automatically adjust the heat up time throughout the year, saving you energy.

### Temperature Hold Facility

This function allows you to hold a set temperature for a specific duration - ideal for parties. After the hold duration, the thermostat will revert back to the programmed setting.

### Holiday Function

The holiday function reduces the set temperature in your home for the duration of your holiday. At the end of your holiday, the thermostat will revert back to the programmed setting, ensuring your home is warm on your return.

### Temperature Override

The override facility allows you to adjust the desired temperature in your home without the need to fully re-program the thermostat. This new set temperature will be maintained until the next programmed setting. An override limit function allows you to limit the use of temperature override keys.

### Technical:

Temperature Range:	05-35 °C; 05-95 °F
5/2 Day Programming Mode:	Yes
7 Day Programming Mode:	Yes
No of Heating Levels:	4
Optimum Start:	Yes
Holiday Function:	Yes
Keylock Function:	Yes
Temperature Hold Function:	Yes
Temperature Override:	Yes
Temperature Override Limit:	Yes
Frost Protection:	Yes
°C / °F Option:	Yes
Built In Air Sensor:	Yes
Floor Sensing Mode:	Yes
Floor Sensor Included:	Yes
Max Switching Current:	13A
Accuracy:	+/-1 °C
Adjustable Switching Differential:	Yes
Supply:	230v
Dimensions:	98x85x13mm
Weight:	195g